Crimping tools for wire end ferrules

- For wire-end ferrules with and without plastic collars, according to DIN 46228 T.1 and T.4 (~ AWG 24...16)
- Ratchet for precise crimping.
- Release option in the event of incorrect operation

PZ 4

0.5...4 mm²



- Only one crimping station for the whole crosssection range
- Wire-end ferrule insertion from the side

PZ 6/5

0.25...6 mm²



- Crimp complies with Euro-Norm EN 60947-1
- Approval according to VG 95211 (military designation VG 95 236 T 14 B 002)
- Five crimping stations corresponding to the conductor cross-sections
- Wire-end ferrule insertion from the side





Technical data

Description of contact	
Type of contact	
Crimping range	mm²
Crimping range 1 (with multiple crimping positions)	mm ²
Crimping range 2 (with multiple crimping positions)	mm²
Crimping range 3 (with multiple crimping positions)	mm ²
Crimping range 4 (with multiple crimping positions)	mm²
Crimping range 5 (with multiple crimping positions)	mm ²
Tool data	
Length	mm
Weight	g
Note	

PZ 4
Wire-end ferrules with/without plastic collars
0.54
200
448

PZ 6/5			
Wire-end ferrules with/without plastic collars			
0.256			
0.250.5			
0.751.5			
2.5			
4			
6			
200			
423			

Ordering data

or acrining	data	
Version		
VCI 31011		

Туре	Qty	Order No.
PZ 4	1	9012500000

Туре	Qty	Order No.
PZ 6/5	1	9011460000

Note			

Weidmüller **ॐ**

Additional accessories can be found in Chapter J.

Additional accessories can be found in Chapter J.

D.8