



Circuit diagram

Model: LP9033560		Overcharge Detection Voltage(V)	4.28±0.05
Min.Capacity 最低容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V)	2.3±0.1
1900		过放保护电压(V)	
Typical Capacity 典型容量(mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)		Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 2 (A)	constant (A) 持续 1 (A)
2000		Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 2 (A)	constant (A) 持续 1 (A)
Nominal Voltage 标称电压(V)		Battery protection Related Value: (相关的电池保护值)	
3.7			
Internal impedance 内阻(≅) (mΩ,AC 1KHz)			
180			
Charge Temp.充电温度(°C)		Ambient Conditions (环境温度)	
0~45		Discharge Temp.放电温度(°C)	
-20~60°		Humidity(湿度)	
65±20%			

		Drawn:	Moyongdi	Revise No.:	E4-2009
Title	LP9033560-PCM-LD/	Checked 1:	Jane	Projection:	
File NO.	A04407	Checked 2:	Keyan	Page:	1/1
		Approved:		Scale:	1 : 1
		Draw Date:	2011/03/17	Unit:	mm

Remark(备注):  
1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).  
2. RoHS compliant (严格按照ROHS要求生产).