


# Current Probes

## A621 • A622 Data Sheet



A621



A622

## Features & Benefits

### A621

- AC - 5 Hz to 50 kHz
- 100 mA to 2000 A Peak
- For DMM's and Oscilloscopes
- Clamp On

### A622

- AC/DC - 100 kHz
- 50 mA to 100 A Peak
- For DMM's and Oscilloscopes

## Applications

- Motor Drives
- Inverters
- Power Supplies
- Avionics

The A600 Series current probes high-value current probes are specifically designed to support measurements you make with your DMM, TekMeter® or oscilloscope\*1.

### A621 2000 Amp AC Current Probe/BNC

This industrial-style clamp-on probe has a BNC connector and may be used with a shrouded banana plug adapter\*1 so it can be used on digital multimeters, TekMeter, and scopes. The A621 can measure AC currents from 100 mA to 2000 A peak over a frequency range of 5 Hz to 50 kHz. It provides a 1 mV, 10 mV, or 100 mV output for each Amp measured.

### A622 100 Amp AC/DC Current Probe/BNC

This "long nose" style clamp-on probe uses a Hall Effect current sensor to provide a voltage output to oscilloscopes. It has a BNC connector and may be used with a shrouded banana plug adapter\*1 so it can also be used on digital multimeters, TekMeter, and scopes. The A622 can measure AC/DC currents from 50 mA to 100 A peak over a frequency range of DC to 100 kHz. It provides 10 mV or 100 mV output for each Amp measured.

\*1 For instruments with banana jack inputs, Tektronix part number 012-1450-00 Female BNC to banana lead adapter is required.

**Probe Compatibility Chart**

Part #	Description	DMM100*1	DMM200*1	DMM910*1	THS700*1	TX3/TX1*1
A621	AC Current Probe, 2000 A	Yes	Yes	Yes	Yes	Yes
A622	AC/DC Current Probe, 100 A	Yes	Yes	Yes	Yes	Yes

\*1 For instruments with banana jack inputs, Tektronix part number 012-1450-00 Female BNC to banana lead adapter is required.

**Typical Characteristics**

	A621	A622
Frequency Range	5 Hz to 50 kHz	DC to 100 kHz
Max. Input Current	2000 A peak	100 A peak
Output	1 mV/A, 10 mV/A, 100 mV/A	10 mV/A, 100 mV/A
Max. Conductor Diameter	54 mm (2.13 in.)	11.8 mm (0.46 in.)
Termination	BNC*1	BNC*1
Max. Bare Wire Voltage	600 V (CATIII)	600 V (CATIII)
Safety	UL3111-2-032 CSA1010.2.032 EN61010-2-032 IEC61010-2-032	UL3111-2-032 CSA1010.2.032 EN61010-2-032 IEC61010-2-032

\*1 For instruments with banana jack inputs, Tektronix part number 012-1450-00 Female BNC to banana lead adapter is required.

**Ordering Information**


**A621**  
2000 A AC Current Probe/BNC.

**A622**  
100 A AC/DC Current Probe/BNC.

**Service**  
Opt. R3 – Repair Service 3 Years  
Opt. R5 – Repair Service 5 Years

**Recommended Accessories**

**A621, A622**  
Adapter, lead; discrete – MLD, 2, 18 AWG, dual insul, BNC, female X 4 mm dual insul; banana jack X dual insul plug, shield banana. Order 012-1450-xx.



Product(s) are manufactured in ISO registered facilities.



**Contact Tektronix:**

- ASEAN / Australasia** (65) 6356 3900
- Austria** +41 52 675 3777
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 07 81 60166
- Brazil** +55 (11) 40669400
- Canada** 1 (800) 661-5625
- Central East Europe, Ukraine, and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** +33 (0) 1 69 86 81 81
- Germany** +49 (221) 94 77 400
- Hong Kong** (852) 2585-6688
- India** (91) 80-42922600
- Italy** +39 (02) 25086 1
- Japan** 81 (3) 6714-3010
- Luxembourg** +44 (0) 1344 392400
- Mexico, Central/South America & Caribbean** 52 (55) 54247900
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 090 02 021797
- Norway** 800 16098
- People's Republic of China** 86 (10) 6235 1230
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 82 (2) 6917-5000
- Russia & CIS** +7 (495) 7484900
- South Africa** +27 11 206 8360
- Spain** (+34) 901 988 054
- Sweden** 020 08 80371
- Switzerland** +41 52 675 3777
- Taiwan** 886 (2) 2722-9622
- United Kingdom & Ireland** +44 (0) 1344 392400
- USA** 1 (800) 426-2200

For other areas contact Tektronix, Inc at: 1 (503) 627-7111

Updated 30 October 2008

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com)



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

14 Jan 2009

60W-15081-0c

