

# BC307B, BC307C

## Amplifier Transistors

PNP Silicon



ON Semiconductor



<http://onsemi.com>

### MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	$V_{CEO}$	-45	Vdc
Collector-Base Voltage	$V_{CBO}$	-50	Vdc
Emitter-Base Voltage	$V_{EBO}$	-5.0	Vdc
Collector Current — Continuous	$I_C$	-100	mAdc
Total Device Dissipation @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	350 2.8	mW mW/ $^\circ\text{C}$
Total Device Dissipation @ $T_C = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	$P_D$	1.0 8.0	Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	$T_J, T_{stg}$	-55 to +150	$^\circ\text{C}$

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	357	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction to Case	$R_{\theta JC}$	125	$^\circ\text{C}/\text{W}$



CASE 29  
TO-92  
STYLE 17

### ORDERING INFORMATION

Device	Package	Shipping
BC307B	TO-92	5000 Units/Box
BC307BRL1	TO-92	2000/Tape & Reel
BC307BZL1	TO-92	2000/Ammo Pack
BC307C	TO-92	5000 Units/Box

# BC307B, BC307C

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

### OFF CHARACTERISTICS

Collector–Emitter Breakdown Voltage (I <sub>C</sub> = –2.0 mA <sub>dc</sub> , I <sub>B</sub> = 0)	V <sub>(BR)CEO</sub>	–45	—	—	V <sub>dc</sub>
Emitter–Base Breakdown Voltage (I <sub>E</sub> = –100 μA <sub>dc</sub> , I <sub>C</sub> = 0)	V <sub>(BR)EBO</sub>	–5.0	—	—	V <sub>dc</sub>
Collector–Emitter Leakage Current (V <sub>CES</sub> = –50 V, V <sub>BE</sub> = 0) (V <sub>CES</sub> = –50 V, V <sub>BE</sub> = 0) T <sub>A</sub> = 125°C	I <sub>CES</sub>	—	–0.2	–15	nA <sub>dc</sub> μA

### ON CHARACTERISTICS

DC Current Gain (I <sub>C</sub> = –10 μA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> )		h <sub>FE</sub>			
BC307B		—	150	—	—
BC307C		—	270	—	—
(I <sub>C</sub> = –2.0 mA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> )	BC307	120	—	800	—
	BC307B	200	290	460	—
	BC307C	420	500	800	—
(I <sub>C</sub> = –100 mA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> )	BC307B	—	180	—	—
	BC307C	—	300	—	—
Collector–Emitter Saturation Voltage (I <sub>C</sub> = –10 mA <sub>dc</sub> , I <sub>B</sub> = –0.5 mA <sub>dc</sub> ) (I <sub>C</sub> = –10 mA <sub>dc</sub> , I <sub>B</sub> = see Note 1) (I <sub>C</sub> = –100 mA <sub>dc</sub> , I <sub>B</sub> = –5.0 mA <sub>dc</sub> )	V <sub>CE(sat)</sub>	—	–0.10	–0.3	V <sub>dc</sub>
		—	–0.30	–0.6	—
		—	–0.25	—	—
Base–Emitter Saturation Voltage (I <sub>C</sub> = –10 mA <sub>dc</sub> , I <sub>B</sub> = –0.5 mA <sub>dc</sub> ) (I <sub>C</sub> = –100 mA <sub>dc</sub> , I <sub>B</sub> = –5.0 mA <sub>dc</sub> )	V <sub>BE(sat)</sub>	—	–0.7	—	V <sub>dc</sub>
		—	–1.0	—	—
Base–Emitter On Voltage (I <sub>C</sub> = –2.0 mA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> )	V <sub>BE(on)</sub>	–0.55	–0.62	–0.7	V <sub>dc</sub>

### DYNAMIC CHARACTERISTICS

Current–Gain — Bandwidth Product (I <sub>C</sub> = –10 mA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> , f = 100 MHz)	f <sub>T</sub>	—	280	—	MHz
Common Base Capacitance (V <sub>CB</sub> = –10 V <sub>dc</sub> , I <sub>C</sub> = 0, f = 1.0 MHz)	C <sub>cbo</sub>	—	—	6.0	pF
Noise Figure (I <sub>C</sub> = –0.2 mA <sub>dc</sub> , V <sub>CE</sub> = –5.0 V <sub>dc</sub> , R <sub>S</sub> = 2.0 kΩ, f = 1.0 kHz)	NF	—	2.0	10	dB

1. I<sub>C</sub> = –10 mA<sub>dc</sub> on the constant base current characteristic, which yields the point I<sub>C</sub> = –11 mA<sub>dc</sub>, V<sub>CE</sub> = –1.0 V.

# BC307B, BC307C

## TYPICAL CHARACTERISTICS




Figure 1. Normalized DC Current Gain




Figure 2. "Saturation" and "On" Voltages




Figure 3. Current-Gain — Bandwidth Product




Figure 4. Capacitances




Figure 5. Output Admittance






Figure 6. Base Spreading Resistance

# BC307B, BC307C

## PACKAGE DIMENSIONS

TO-92  
(TO-226)  
CASE 29-11  
ISSUE AL




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---

STYLE 17:

1. COLLECTOR
2. BASE
3. EMITTER

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

### PUBLICATION ORDERING INFORMATION

**Literature Fulfillment:**

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** ONlit@hibbertco.com

**N. American Technical Support:** 800-282-9855 Toll Free USA/Canada

**JAPAN:** ON Semiconductor, Japan Customer Focus Center  
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031  
**Phone:** 81-3-5740-2700  
**Email:** r14525@onsemi.com

**ON Semiconductor Website:** <http://onsemi.com>

For additional information, please contact your local Sales Representative.