

350W Enclosed Power Supply



Key Features:

- ▲ AC input range selectable by switch
- ▲ Forced air cooling by built-in DC fan
- ▲ Protections: short circuit/over load/over voltage/over temperature
- ▲ 2-Years Product Warranty

Input Voltage	90-132VAC/176-264VAC
Input Frequency	47-63 Hz
Inrush Current	20A MAX.(115VAC)/ 40A max.(230VAC)
Input Leakage Current	<3.5mA/240VAC
Line Regulation	±0.5%
Hold-up Time	20 ms min
Protection Over Load	105-140%rated output power
Operating Temperature	-10°C to +60°C
Storage Temperature	-25°C to +85°C
Safety Standards	UL60950-1,EN60950-1
EMI(Conduction & Radiation Disturbance)	EN 55011 classB EN55022 class B
Dimension (LxWxH)	215X115X50mm
Weight	1110g

Model	DC output		Tol.	R&N	Efficiency
ESE350-5	5V	60A	±2%	100mV	76%
ESE350-12	12V	29A	±2%	120mV	84%
ESE350-24	24V	14.6A	±1%	150mV	85%
ESE350-36	36V	9.72A	±1%	200mV	86%
ESE350-48	48V	7.3A	±1%	200mV	86%