

DC FAN

JAMICON

120x120x38 mm

JF1238-13 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : $\pm 10\%$

• SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)		
JF1238B1TR13	Dual Ball	12	10.2 ~ 13.8	168.9	0.566	4000	1.33	15.96	1.50	53.2	265		
JF1238B1UR13				151.17	0.459	3600	0.93	11.16	1.00	50.6			
JF1238B1SR13				135.8	0.356	3200	0.70	8.40	0.80	47.9			
JF1238-1HR13	B, S			118.7	0.281	2800	0.48	5.76	0.55	43.8			
JF1238-1MR13				101.3	0.213	2400	0.32	3.96	0.38	39.1			
JF1238-1LR13				84.5	0.155	2000	0.20	2.40	0.21	33.8			
JF1238-1ER13				69.6	0.109	1700	0.10	1.20	0.11	29.6			
JF1238B2TR13	Dual Ball			24	20.4 ~ 27.6	168.9	0.566	4000	0.53	12.72		0.60	53.2
JF1238B2UR13						151.17	0.459	3600	0.42	10.08		0.46	50.6
JF1238B2SR13						135.8	0.356	3200	0.37	8.88		0.45	47.9
JF1238-2HR13	B, S					118.7	0.281	2800	0.31	7.44		0.32	43.8
JF1238-2MR13						101.3	0.213	2400	0.22	5.28		0.23	39.1
JF1238-2LR13		84.5	0.155			2000	0.13	3.12	0.14	33.8			
JF1238-2ER13		69.6	0.109			1700	0.09	2.16	0.11	29.6			
JF1238B4TR13	Dual Ball	48	40.8 ~ 60.0			168.9	0.566	4000	0.29	13.92	0.32	53.2	
JF1238B4UR13						151.17	0.459	3600	0.23	11.04	0.25	50.6	
JF1238B4SR13						135.8	0.356	3200	0.20	9.60	0.22	47.9	
JF1238B4HR13						118.7	0.281	2800	0.13	6.24	0.15	43.8	
JF1238B4MR13						101.3	0.213	2400	0.09	4.32	0.11	39.1	
JF1238B4LR13				84.5	0.155	2000	0.07	3.36	0.08	33.8			

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page “PART NUMBER SYSTEM”.

Please contact us for detail if your request bearing system is not shown in the above list

