


KS M20G

Кабельные вводы


Material

TPE and Polyamide 66 - Halogen Free
 UL approved material
 Integrated cable anchorage,
 wide sealing range.
 Material thickness 1,5 - 5 mm
 Material thickness IP67/65 2 - 5 mm
 Quick and simple assembly without
 the use of tools.

Mode of protection


IP67 / IP65


Temperature range

-20°C...+125°C ⁽¹⁾

Test standard

EN60529:1991+A1
 EN50262:1998
 EMKO-TUI (03-SEC) FI001/84
 606620

Semko report


E-number	Size	IP67 and Cable Anchorage Type A* for Cable Ø mm	IP65 for Cable Ø mm	A mm	B for IP67/65 mm	H mm	H2 mm	D1 mm	D*** mm	Pcs pack	
RAL 7035											
T_14 758 03	M20	7 - 11	4 - 11	20,5	2 - 5	17 - 20	5,5	4,0	29,3 - 34,5	50	2500
T_14 758 04	M25	7 - 13**	4 - 13	25,5	2 - 5	17 - 20	5,7	5,0	34,3 - 40,0	50	2000
RAL 9005											
T_14 758 13	M20	7 - 11	4 - 11	20,5	2 - 5	17 - 20	5,5	4,0	29,3 - 34,5	50	2500
T_14 758 14	M25	7 - 13**	4 - 13	25,5	2 - 5	17 - 20	5,7	5,0	34,3 - 40,0	50	2000
RAL 9010											
T_14 758 23	M20	7 - 11	4 - 11	20,5	2 - 5	17 - 20	5,5	4,0	29,3 - 34,5	50	2500
T_14 758 24	M25	7 - 13**	4 - 13	25,5	2 - 5	17 - 20	5,7	5,0	34,3 - 40,0	50	2000
RAL XYZ											
TKS M20 XYZ	M20	7 - 11	4 - 11	20,5	2 - 5	17 - 20	5,5	4,0	29,3 - 34,5	50	2500
TKS M25 XYZ	M25	7 - 13**	4 - 13	25,5	2 - 5	17 - 20	5,7	5,0	34,3 - 40,0	50	2000

<http://www.tappersealingtechnology.com/web/tst.aspx>

http://www.tappersealingtechnology.com/web/Product_Catalogue_Q3_2009.aspx