PRODUCT SPECIFICATION

DATE: 11/13/03'

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY: KSA215AC8	NO. 58083215	REV. 4
		SHEET 1 OF 2	

1. OUTSIDE DIMENSION : UNIT (mm)



2. SCHEMATIC : TOP VIEW



PRODUCT SPECIFICATION

DATE: 11/13/03'

COSMO ELECTRONICS CORPORATION	SOLID STATE RELAY: KSA215AC8	NO. 58083215	REV. 4
		SHEET 2 OF 2	

3. Absolute Maximum Ratings

(Ta=25℃)

Parameter		Symbol	Rating	Unit
Input	Input signal voltage	V_{IN}	100~240	VAC
	Drop-out voltage	Vdo	10	VAC
Output	RMS on-state current	I_T	15	Arms
	Peak one cycle surge current (8.3ms)	Isurge	150	A
	Repetitive peak-off state voltage	V_{DRM}	600	V
	Operating frequency	f	47~70	Hz
	Critical rate of rise of on-state current	di/dt	50	A/us
	Load supply voltage	Vout	250	Vrms AC
Isolation voltage input to output		Viso	4000	Vrms
Operating temperature		Topr	-30~100	℃
Storage temperature		Tstg	-30~125	℃
Soldering temperature 10sec		Tsol	300	℃

4. Electro-optical Characteristics

(Ta=25℃)

Parameter		Symbol	Conditions	MIN	TYP	MAX	Unit
Input	Pick-up voltage	Vpu	Rin=11KΩ			100	VAC
	Input current	Rin			11		KΩ
Output	On-state voltage	V_T	I_T=1Arms			1.5	Vrms
	Operating current	Iop	Vout=220Vrms	50			mArms
	Leakage current	Ileak	Vout=220Vrms		3.5	8	mArms
	Critical rate of rise of off-state voltage	dv/dt		100			V/us
	Zero-cross				YES		
	Load Voltage Rating	Vout	I_T =50mArms MIN	50		280	VAC
Minimum trigger current		I_{FT}	V_{DRM}=600V			25	mA
Isolation resistance input to output		R_{ISO}	DC500V	10			GΩ
Turn-on time		Ton	60Hz AC			8.3	ms
Turn-off time		Toff	60Hz AC			8.3	ms
Thermal resistance (between junction and case)		Rth (j-c)1			2.5		℃/W