



Bluegiga Wi-Fi
Modules



Embedded Wi-Fi modules
for affordable connectivity

Bluegiga WF111 Wi-Fi® Module

WF111 provides a low cost and simple Wi-Fi solution for devices that run Linux operating system and a TCP/IP stack, offering all the benefits of a module – small form factor, easy integration and certifications.

bluegiga

www.bluegiga.com

WF111

Wi-Fi Module™



Key Features

- IEEE 802.11 b/g/n radio
 - Single 2.4 GHz band
 - Symbol rate up to 72.2Mbps
- Integrated antenna or U.FL connector
- Support for WEP, WPA and WPA2 encryption
- Software Access Point mode
- Advanced *Bluetooth* coexistence support
- Temperature range: -40°C - +85°C
- SDIO host interface
- Fully CE, FCC and IC qualified
- Linux operating system drivers for ARM and X86 processors.
- Low power solution designed for mobile and battery power applications
- Small size: 12.0 x 19.0 x 2.1 mm

Description

A fully integrated single 2.4GHz band 802.11 b/g/n module for portable and battery powered applications. WF111 integrates an IEEE 802.11 b/g/n radio, antenna or U.FL antenna connector and SDIO host interface.

WF111 provides a low cost and simple Wi-Fi solution for devices that run an operating system and a TCP/IP stack, still offering the benefits of a module – compact size, easy integration, Linux drivers for ARM and X86, and certifications. WF111 has support for Wi-Fi encryption protocols and for various co-existence schemes enabling exceptional performance during simultaneous use of IEEE 802.11 and *Bluetooth* with a single antenna.

Benefits

- Small, fully integrated 802.11 b/g/n module with radio and antenna
- Compact size, low power solution designed for mobile and battery power applications
- Industrial specifications, long life time and future proof solution
- Regulatory qualifications reducing R&D risk and time-to-market

Applications

For professional applications requiring reliable, small size, long range Wi-Fi connectivity for Linux with SDIO. Applications include: Point of Sale, automotive aftermarket, eHealth/medical, audio and many others.

Choosing Bluegiga will save your resources, time and money.



1. State-of-the-art and reliable hardware.

2. Professional and agile technical support and design review services.

Radio and Modem

Symbol rates	IEEE 802.11n : 72.2, 65, 58.5, 57.8, 52, 43.3, 39, 28.9, 26, 21.7, 19.5, 14.4, 13, 7.2, 6.5Mbps IEEE 802.11g : 54, 48, 36, 24, 18, 12, 9, 6Mbps IEEE 802.11b : 11, 5.5, 2, 1Mbps
Modulation	CCK, DSSS, OFDM with BPSK, QPSK, 16-QAM and 64-QAM
Frequency	2.4GHz to 2.497GHz
Channels	N. America: 11 channels, Rest of the world: 13 channels
QoS	WMM, WMM Power Save (WMM-PS)

Security

Encryption	WPA / WPA2, WEP, CCMP (AES), TKIP WPS
------------	--

Hardware

Host interfaces	SDIO 4-bit, SDIO 1-bit, CSPI
Power supply	Two voltages required: 3.3V, 1.8V <ul style="list-style-type: none">• Core voltage: 1,45–2,0 V• Front end power supply: 2.7–4.8V• Digital I/O lines: 1,7–3,6V
Antenna	Internal, U.FL connector
Dimensions	12.0 x 19.0 x 2.1 mm
Package	Surface mount

Software

OS drivers	SDIO drivers for Linux 2.6 and 3.x kernels
------------	--

Wi-Fi Modules comparison chart

WF111



WF121



Radio performance		
Typical TX power	+17 dBm	+17 dBm
Typical RX sensitivity	-91 dBm	-91 dBm
Line of sight range	300-500m	300-500m
Host Interfaces		
SDIO	Yes	No
CSPI	Yes	No
UART	No	Yes
USB	No	Yes *
Peripheral Interfaces		
SPI	-	up to 2*
UART	-	up to 4*
USB	-	1xOTG*
Ethernet MAC	-	1*
I2C	-	up to 2*
GPIO	6	up to 38
AIO	-	up to 10*
Microcontroller		
Architecture	-	MIPS 4K
MHz	-	80 Mhz
RAM	-	128 kB (64 kB free)
Flash	-	512 kB (256 kB free)
Operating voltage		
Operating voltage	1.8V and 3.3V	2.7V - 3.6V
Bluegiga APIs		
Bluegiga BGAPI binary protocol	-	Yes
Bluegiga BGLib host library	-	Yes
OS drivers		
Linux	Yes	Not needed
Windows	-	Not needed
Software development		
On-board applications	-	Yes
Bluegiga BGScript support	-	Yes
Firmware development service	-	Yes
SDK	Linux wireless tools	Bluegiga SDK
Dimensions		
Dimensions (W x L x H)	12.0 x 19.0 x 2.1 mm	15.4 x 26.2 x 2.1 mm

* check availability schedule for software support

For more detailed information please refer to a separate Bluegiga Wi-Fi modules comparison chart.

© Bluegiga Technologies 2012.

Bluegiga Technologies takes no responsibility for any mistakes that might appear in this document. It reserves the right to change devices, software or specifications detailed here at any time without notice, and does not make any commitment to update the information contained here.

Bluegiga products are not authorised for any use as critical components in life support devices or systems.

The *Bluetooth* trademark and logo are registered trademarks and are owned by the Bluetooth SIG, Inc. Wi-Fi is a Registered Trademark of a Wi-Fi alliance.

Finland Office
Sinikalliontie 5 A , 02630 Espoo,
Finland
Phone: +358 9 435 50 60,

USA Office
3235 Satellite Boulevard, Building
400, Suite 300,
Duluth, GA, 30096, USA

Hong Kong Office
43/f , AIA Tower, 183 Electric Road,
North Point,
Hong Kong

