



MEAN WELL

SWITCHING POWER SUPPLY


ISO-9001 CERTIFIED MANUFACTURER

SMU01N-B SERIES

- | | |
|------------------------------|----------------------------------|
| .UNREGULATED DC OUTPUT | .NO EXTERNAL COMPONENTS REQUIRED |
| .1000VDC I/O ISOLATION | .HIGH RELIABILITY / LOW COST |
| .INPUT FILTER:CAPACITOR TYPE | .100% BURN-IN TEST |
| .INTERNAL SMD TECHNOLOGY | .MTBF:700,000 HOURS |

ORDER NO.	SMU01N-05B	SMU01N-09B	SMU01N-12B	SMU01N-15B
SPECIFICATION				
DC OUTPUT VOLTAGE	5V	9V	12V	15V
OUTPUT VOLTAGE ACCURACY	±2%			
OUTPUT RATED CURRENT	200mA	110mA	84mA	67mA
OUTPUT CURRENT RANGE	0-200mA	0-110mA	0-84mA	0-67mA
RIPPLE & NOISE	100mVp-p (max.)			
LINE REGULATION	±1.2% FOR 1% INPUT VARIATION			
LOAD REGULATION	±8% @ 20%-FULL LOAD			
DC OUTPUT POWER	1W	1W	1W	1W
EFFICIENCY	73%	77%	77%	80%
SWITCHING FREQUENCY	100KHz min.			
INPUT VOLTAGE RANGE	24 ±10% (21.6-26.4VDC)			
INPUT CURRENT	57mA max.			
SHORT CIRCUIT PROTECTION	MOMENTARY			
OVER VOLTAGE PROTECTION	-----			
TEMP. COEFFICIENT	±0.03% / °C (0-50°C)			
ISOLATION VOLTAGE	I/P-O/P:1 KVDC MIN.			
ISOLATION RESISTANCE	I/P-O/P:500VDC / 100M Ohms MIN.			
ISOLATION CAPACITANCE	80pF max.			
WORKING TEMP., HUMIDITY	-25°C~+60°C, 20%~90% RH (NO DERATING); 80% LOAD @ 71°C			
STORAGE TEMP., HUMIDITY	-40°C~+105°C, 10%~95% RH			
DIMENSION	0.46 ""0.40 ""0.30 ""			
WEIGHT	1.3 g			
CASE METERIAL	NON-CONDUCTIVE PLASTIC			

MECHANISM AND PIN CONFIGURATION



NOTE : 1.ALL PARAMETERS ARE SPECIFIED AT RATED INPUT, RATED LOAD, 25°C 70% RH. AMBIENT.
 2.RIPPLE & NOISE ARE MEASURED AT 20MHz BY USING A 12" TWISTED PAIR TERMINATED WITH A 0.1uF & 47uF CAPACITOR.
 3.LINE REGULATION IS MEASURED FROM LOW LINE TO HIGH LINE AT RATED LOAD.
 4.LOAD REGULATION IS MEASURED FROM 20% TO 100% RATED LOAD.