

Warehouse Name* - При клике левой клавишей мыши по одной из строк столбца "Warehouse Name", будет выведена информация о наличии компонента на складе.

Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20μs)		Maximum Energy(J)		Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	2Time(A)	1Time(A)	2ms	10/1000(μs)	(W)	(pF)	
FNR-05K180	-40°C~+85°C	18	11	14	40	1	50	100	0.3	0.4	0.01	1600	FNR-05K180
FNR-07K180	-40°C~+85°C	18	11	14	36	2.5	125	250	0.8	0.9	0.02	3500	FNR-07K180
FNR-10K180	-40°C~+85°C	18	11	14	36	5	250	500	1.5	2.1	0.05	7500	FNR-10K180
FNR-14K180	-40°C~+85°C	18	11	14	36	10	500	1000	3.5	4.0	0.1	18000	FNR-14K180
FNR-20K180	-40°C~+85°C	18	11	14	36	20	1000	2000	10.0	11.0	0.2	37000	FNR-20K180
FNR-05K220	-40°C~+85°C	22	14	18	48	1	50	100	0.4	0.5	0.01	1300	FNR-05K220
FNR-07K220	-40°C~+85°C	22	14	18	43	2.5	125	250	0.9	1.1	0.02	2800	FNR-07K220
FNR-10K220	-40°C~+85°C	22	14	18	43	5	250	500	2.0	2.5	0.05	6000	FNR-10K220
FNR-14K220	-40°C~+85°C	22	14	18	43	10	500	1000	4.0	5.0	0.1	15000	FNR-14K220
FNR-20K220	-40°C~+85°C	22	14	18	43	20	1000	2000	13.0	14.0	0.2	30000	FNR-20K220
FNR-05K270	-40°C~+85°C	27	17	22	60	1	50	100	0.5	0.6	0.01	1050	FNR-05K270
FNR-07K270	-40°C~+85°C	27	17	22	53	2.5	125	250	1.0	1.4	0.02	2000	FNR-07K270
FNR-10K270	-40°C~+85°C	27	17	22	53	5	250	500	2.5	3.0	0.05	4000	FNR-10K270
FNR-14K270	-40°C~+85°C	27	17	22	53	10	500	1000	5.0	6.0	0.1	10000	FNR-14K270
FNR-20K270	-40°C~+85°C	27	17	22	53	20	1000	2000	15.0	18.0	0.2	22000	FNR-20K270
FNR-05K330	-40°C~+85°C	33	20	26	73	1	50	100	0.6	0.8	0.01	900	FNR-05K330
FNR-07K330	-40°C~+85°C	33	20	26	65	2.5	125	250	1.2	1.7	0.02	1500	FNR-07K330
FNR-10K330	-40°C~+85°C	33	20	26	65	5	250	500	3.0	4.0	0.05	3000	FNR-10K330
FNR-14K330	-40°C~+85°C	33	20	26	65	10	500	1000	6.0	7.5	0.1	7500	FNR-14K330
FNR-20K330	-40°C~+85°C	33	20	26	65	20	1000	2000	20.0	13.0	0.2	17000	FNR-20K330
FNR-05K390	-40°C~+85°C	39	25	31	86	1	50	100	0.8	0.9	0.01	500	FNR-05K390
FNR-07K390	-40°C~+85°C	39	25	31	77	2.5	125	250	1.5	2.1	0.02	1350	FNR-07K390
FNR-10K390	-40°C~+85°C	39	25	31	77	5	250	500	3.5	4.6	0.05	2600	FNR-10K390
FNR-14K390	-40°C~+85°C	39	25	31	77	10	500	1000	7.0	8.6	0.1	6500	FNR-14K390
FNR-20K390	-40°C~+85°C	39	25	31	77	20	1000	2000	24.0	26.0	0.2	15000	FNR-20K390
FNR-05K470	-40°C~+85°C	47	30	38	104	1	50	100	1.0	1.1	0.01	450	FNR-05K470
FNR-07K470	-40°C~+85°C	47	30	38	93	2.5	125	250	1.8	2.5	0.02	1150	FNR-07K470
FNR-10K470	-40°C~+85°C	47	30	38	93	5	250	500	4.5	5.5	0.05	2200	FNR-10K470
FNR-14K470	-40°C~+85°C	47	30	38	93	10	500	1000	8.5	10.0	0.1	5500	FNR-14K470
FNR-20K470	-40°C~+85°C	47	30	38	93	20	1000	2000	30.0	33.0	0.2	13000	FNR-20K470
FNR-05K560	-40°C~+85°C	56	35	45	123	1	50	100	1.0	1.3	0.01	400	FNR-05K560
FNR-07K560	-40°C~+85°C	56	35	45	110	2.5	125	250	2.2	3.1	0.02	950	FNR-07K560
FNR-10K560	-40°C~+85°C	56	35	45	110	5	250	500	5.5	7.0	0.05	1800	FNR-10K560
FNR-14K560	-40°C~+85°C	56	35	45	110	10	500	1000	10.0	11.0	0.1	4500	FNR-14K560
FNR-20K560	-40°C~+85°C	56	35	45	110	20	1000	2000	35.0	41.0	0.2	110000	FNR-20K560
FNR-05K680	-40°C~+85°C	68	40	56	150	1	50	100	1.2	1.6	0.01	350	FNR-05K680
FNR-07K680	-40°C~+85°C	68	40	56	135	2.5	125	250	2.5	3.6	0.02	700	FNR-07K680
FNR-10K680	-40°C~+85°C	68	40	56	135	5	250	500	6.5	8.2	0.05	1300	FNR-10K680
FNR-14K680	-40°C~+85°C	68	40	56	135	10	500	1000	12.0	14.0	0.1	3300	FNR-14K680
FNR-20K680	-40°C~+85°C	68	40	56	135	20	1000	2000	40.0	46.0	0.2	7000	FNR-20K680
FNR-05K820	-40°C~+85°C	82	50	65	145	1	50	100	1.7	2.5	0.1	250	FNR-05K820
FNR-07K820	-40°C~+85°C	82	50	65	135	2.5	125	250	3.5	5.5	0.25	550	FNR-07K820
FNR-10K820	-40°C~+85°C	82	50	65	135	5	250	500	8.0	12.0	0.4	1800	FNR-10K820
FNR-14K820	-40°C~+85°C	82	50	65	135	10	500	1000	14.0	22.0	0.6	2900	FNR-14K820
FNR-20K820	-40°C~+85°C	82	50	65	135	20	1000	2000	27.0	38.0	1.0	5500	FNR-20K820
FNR-05K101	-40°C~+85°C	100	60	85	175	1	50	100	2.0	3.0	0.1	200	FNR-05K101

Warehouse Name* - При клике левой клавишей мыши по одной из строк столбца "Warehouse Name", будет выведена информация о наличии компонента на складе.

Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20μs)		Maximum Energy(J)		Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	2Time(A)	1Time(A)	2ms	10/1000(μs)	(W)	(pF)	
FNR-07K101	-40°C~+85°C	100	60	85	165	2.5	125	250	4.0	6.5	0.25	500	FNR-07K101
FNR-10K101	-40°C~+85°C	100	60	85	165	5	250	500	10.0	15.0	0.4	1400	FNR-10K101
FNR-14K101	-40°C~+85°C	100	60	85	165	10	500	1000	18.0	28.0	0.5	2400	FNR-14K101
FNR-20K101	-40°C~+85°C	100	60	85	165	20	1000	2000	30.0	45.0	1.0	4800	FNR-20K101
FNR-05K121	-40°C~+85°C	120	75	100	210	5	200	400	2.5	4.0	0.1	170	FNR-05K121
FNR-07K121	-40°C~+85°C	120	75	100	200	10	600	1200	5.0	4.8	0.25	450	FNR-07K121
FNR-10K121	-40°C~+85°C	120	75	100	200	25	1250	2500	12.0	18.0	0.4	1100	FNR-10K121
FNR-14K121	-40°C~+85°C	120	75	100	200	50	2500	4500	20.0	32.0	0.6	1900	FNR-14K121
FNR-20K121	-40°C~+85°C	120	75	100	200	100	4000	6500	40.0	55.0	1.0	3800	FNR-20K121
FNR-05K151	-40°C~+85°C	150	95	125	260	5	200	400	3.0	4.8	0.1	140	FNR-05K151
FNR-07K151	-40°C~+85°C	150	95	125	250	10	600	1200	6.0	9.7	0.25	350	FNR-07K151
FNR-10K151	-40°C~+85°C	150	95	125	250	25	1250	2500	16.0	22.0	0.4	900	FNR-10K151
FNR-14K151	-40°C~+85°C	150	95	125	250	50	2500	4500	25.0	40.0	0.6	1500	FNR-14K151
FNR-20K151	-40°C~+85°C	150	95	125	250	100	4000	6500	50.0	70.0	1.0	3000	FNR-20K151
FNR-05K181	-40°C~+85°C	180	115	150	315	5	200	400	3.5	5.5	0.1	110	FNR-05K181
FNR-07K181	-40°C~+85°C	180	115	150	300	10	600	1200	8.0	1.0	0.25	300	FNR-07K181
FNR-10K181	-40°C~+85°C	180	115	150	300	25	1250	2500	18.0	25.0	0.4	700	FNR-10K181
FNR-14K181	-40°C~+85°C	180	115	150	300	50	2500	4500	30.0	50.0	0.6	1250	FNR-14K181
FNR-20K181	-40°C~+85°C	180	115	150	300	100	4000	6500	60.0	85.0	1.0	2500	FNR-20K181
FNR-05K201	-40°C~+85°C	200	130	170	355	5	200	400	4.0	6.5	0.1	80	FNR-05K201
FNR-07K201	-40°C~+85°C	200	130	170	340	10	600	1200	10.0	13.0	0.25	250	FNR-07K201
FNR-10K201	-40°C~+85°C	200	130	170	340	25	1250	2500	20.0	30.0	0.4	500	FNR-10K201
FNR-14K201	-40°C~+85°C	200	130	170	340	50	2500	4500	35.0	57.0	0.6	1000	FNR-14K201
FNR-20K201	-40°C~+85°C	200	130	170	340	100	4000	6500	70.0	95.0	1.0	2000	FNR-20K201
FNR-05K221	-40°C~+85°C	220	140	180	380	5	200	400	4.5	7.0	0.1	70	FNR-05K221
FNR-07K221	-40°C~+85°C	220	140	180	360	10	600	1200	10.0	14.0	0.25	250	FNR-07K221
FNR-10K221	-40°C~+85°C	220	140	180	360	25	1250	2500	23.0	32.0	0.4	450	FNR-10K221
FNR-14K221	-40°C~+85°C	220	140	180	360	50	2500	4500	40.0	60.0	0.6	1000	FNR-14K221
FNR-20K221	-40°C~+85°C	220	140	180	360	100	4000	6500	75.0	100.0	1.0	200	FNR-20K221
FNR-05K241	-40°C~+85°C	240	150	200	415	5	200	400	4.5	8.0	0.1	70	FNR-05K241
FNR-07K241	-40°C~+85°C	240	150	200	395	10	600	1200	10.0	15.0	0.25	2000	FNR-07K241
FNR-10K241	-40°C~+85°C	240	150	200	395	25	1250	2500	23.0	35.0	0.4	400	FNR-10K241
FNR-14K241	-40°C~+85°C	240	150	200	395	50	2500	4500	40.0	63.0	0.6	900	FNR-14K241
FNR-20K241	-40°C~+85°C	240	150	200	395	100	4000	6500	80.0	108.0	1.0	1800	FNR-20K241
FNR-05K271	-40°C~+85°C	270	175	225	475	5	200	400	6.0	8.5	0.1	65	FNR-05K271
FNR-07K271	-40°C~+85°C	270	175	225	455	10	600	1200	12.0	18.0	0.25	170	FNR-07K271
FNR-10K271	-40°C~+85°C	270	175	225	455	25	1250	2500	30.0	40.0	0.4	350	FNR-10K271
FNR-14K271	-40°C~+85°C	270	175	225	455	50	2500	4500	50.0	70.0	0.6	750	FNR-14K271
FNR-20K271	-40°C~+85°C	270	175	225	455	100	4000	6500	90.0	127.0	1.0	1600	FNR-20K271
FNR-05K301	-40°C~+85°C	300	200	250	525	5	200	400	6.0	9.0	0.1	55	FNR-05K301
FNR-07K301	-40°C~+85°C	300	200	250	500	10	600	1200	13.0	20.8	0.25	150	FNR-07K301
FNR-10K301	-40°C~+85°C	300	200	250	500	25	1250	2500	27.0	42.0	0.4	325	FNR-10K301
FNR-14K301	-40°C~+85°C	300	200	250	500	50	2500	4500	55.0	75.0	0.6	650	FNR-14K301
FNR-20K301	-40°C~+85°C	300	200	250	500	100	4000	6500	105.0	135.0	1.0	1400	FNR-20K301
FNR-05K331	-40°C~+85°C	330	210	275	580	5	200	400	6.5	9.0	0.1	60	FNR-05K331
FNR-07K331	-40°C~+85°C	330	210	275	550	10	600	1200	14.5	22.0	0.25	150	FNR-07K331

Warehouse Name** - При клике левой клавишей мыши по одной из строк столбца "Warehouse Name", будет выведена информация о наличии компонента на складе.

Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20µs)		Maximum Energy(J)		Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	2Time(A)	1Time(A)	2ms	10/1000(µs)	(W)	(pF)	
FNR-10K331	-40°C~+85°C	330	210	275	550	25	1250	2500	30.0	44.0	0.4	325	FNR-10K331
FNR-14K331	-40°C~+85°C	330	210	275	550	50	2500	4500	60.0	80.0	0.6	650	FNR-14K331
FNR-20K331	-40°C~+85°C	330	210	275	550	100	4000	6500	105.0	155.0	1.0	1400	FNR-20K331
FNR-05K361	-40°C~+85°C	360	230	300	620	5	200	400	7.5	10.0	0.1	50	FNR-05K361
FNR-07K361	-40°C~+85°C	360	230	300	595	10	600	1200	15.0	25.0	0.25	130	FNR-07K361
FNR-10K361	-40°C~+85°C	360	230	300	595	25	1250	2500	25.0	47.0	0.4	300	FNR-10K361
FNR-14K361	-40°C~+85°C	360	230	300	595	50	2500	4500	65.0	93.0	0.6	550	FNR-14K361
FNR-20K361	-40°C~+85°C	360	230	300	595	100	4000	6500	120.0	163.0	1.0	1200	FNR-20K361
FNR-05K391	-40°C~+85°C	390	250	320	675	5	200	400	8.0	12.0	0.1	50	FNR-05K391
FNR-07K391	-40°C~+85°C	390	250	320	650	10	600	1200	17.0	25.0	0.25	130	FNR-07K391
FNR-10K391	-40°C~+85°C	390	250	320	650	25	1250	2500	40.0	60.0	0.4	270	FNR-10K391
FNR-14K391	-40°C~+85°C	390	250	320	650	50	2500	4500	70.0	100.0	0.6	500	FNR-14K391
FNR-20K391	-40°C~+85°C	390	250	320	650	100	4000	6500	130.0	180.0	1.0	1000	FNR-20K391
FNR-05K431	-40°C~+85°C	430	275	350	745	5	200	400	9.0	13.0	0.1	45	FNR-05K431
FNR-07K431	-40°C~+85°C	430	275	350	710	10	600	1200	20.0	28.0	0.25	110	FNR-07K431
FNR-10K431	-40°C~+85°C	430	275	350	710	25	1250	2500	45.0	65.0	0.4	250	FNR-10K431
FNR-14K431	-40°C~+85°C	430	275	350	710	50	2500	4500	75.0	115.0	0.6	450	FNR-14K431
FNR-20K431	-40°C~+85°C	430	275	350	710	100	4000	6500	140.0	190.0	1.0	900	FNR-20K431
FNR-05K471	-40°C~+85°C	470	300	385	810	5	200	400	10.0	15.0	0.1	40	FNR-05K471
FNR-07K471	-40°C~+85°C	470	300	385	775	10	600	1200	20.0	30.0	0.25	100	FNR-07K471
FNR-10K471	-40°C~+85°C	470	300	385	775	25	1250	2500	45.0	70.0	0.4	230	FNR-10K471
FNR-14K471	-40°C~+85°C	470	300	385	775	50	2500	4500	80.0	125.0	0.6	440	FNR-14K471
FNR-20K471	-40°C~+85°C	470	300	385	775	100	4000	6500	150.0	220.0	1.0	900	FNR-20K471
FNR-10K511	-40°C~+85°C	510	318	415	840	25	1250	2500	45.0	70.0	0.4	200	FNR-10K511
FNR-14K511	-40°C~+85°C	510	318	415	840	50	2500	4500	80.0	125.0	0.6	380	FNR-14K511
FNR-20K511	-40°C~+85°C	510	318	415	840	100	4000	6500	150.0	220.0	1.0	800	FNR-20K511
FNR-10K561	-40°C~+85°C	560	350	455	925	25	1250	2500	45.0	70.0	0.4	180	FNR-10K561
FNR-14K561	-40°C~+85°C	560	350	455	925	50	2500	4500	80.0	125.0	0.6	345	FNR-14K561
FNR-20K561	-40°C~+85°C	560	350	455	925	100	4000	6500	150.0	220.0	1.0	700	FNR-20K561
FNR-10K621	-40°C~+85°C	620	380	505	1025	25	1250	2500	45.0	70.0	0.4	130	FNR-10K621
FNR-14K621	-40°C~+85°C	620	380	505	1025	50	2500	4500	80.0	125.0	0.6	250	FNR-14K621
FNR-20K621	-40°C~+85°C	620	380	505	1025	100	4000	6500	150.0	220.0	1.0	500	FNR-20K621
FNR-10K681	-40°C~+85°C	680	420	560	1120	25	1250	2500	45.0	70.0	0.4	130	FNR-10K681
FNR-14K681	-40°C~+85°C	680	420	560	1120	50	2500	4500	90.0	130.0	0.6	250	FNR-14K681
FNR-20K681	-40°C~+85°C	680	420	560	1120	100	4000	6500	160.0	230.0	1.0	460	FNR-20K681
FNR-10K751	-40°C~+85°C	750	460	615	1240	25	1250	2500	50.0	75.0	0.4	120	FNR-10K751
FNR-14K751	-40°C~+85°C	750	460	615	1240	50	2500	4500	100.0	143.0	0.6	230	FNR-14K751
FNR-20K751	-40°C~+85°C	750	460	615	1240	100	4000	6500	175.0	255.0	1.0	420	FNR-20K751
FNR-10K781	-40°C~+85°C	780	485	640	1290	25	1250	2500	50.0	80.0	0.4	120	FNR-10K781
FNR-14K781	-40°C~+85°C	780	485	640	1290	50	2500	4500	105.0	148.0	0.6	230	FNR-14K781
FNR-20K781	-40°C~+85°C	780	485	640	1290	100	4000	6500	180.0	265.0	1.0	420	FNR-20K781
FNR-10K821	-40°C~+85°C	820	510	670	1355	25	1250	2500	55.0	85.0	0.4	1100	FNR-10K821
FNR-14K821	-40°C~+85°C	820	510	670	1355	50	2500	4500	110.0	157.0	0.6	200	FNR-14K821
FNR-20K821	-40°C~+85°C	820	510	670	1355	100	4000	6500	190.0	282.0	1.0	400	FNR-20K821
FNR-10K911	-40°C~+85°C	910	550	745	1500	25	1250	2500	60.0	93.0	0.4	100	FNR-10K911
FNR-14K911	-40°C~+85°C	910	550	755	1500	50	2500	4500	120.0	175.0	0.6	180	FNR-14K911

Warehouse Name** - При клике левой клавишей мыши по одной из строк столбца "Warehouse Name", будет выведена информация о наличии компонента на складе.

Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20µs)		Maximum Energy(J)		Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	2Time(A)	1Time(A)	2ms	10/1000(µs)	(W)	(pF)	
FNR-20K911	-40°C~+85°C	910	550	755	1500	100	4000	6500	215.0	310.0	1.0	350	FNR-20K911
FNR-10K102	-40°C~+85°C	1000	625	825	1650	25	1250	2500	65.0	102.0	0.4	90	FNR-10K102
FNR-14K102	-40°C~+85°C	1000	625	825	1650	50	2500	4500	130.0	190.0	0.6	150	FNR-14K102
FNR-20K102	-40°C~+85°C	1000	625	825	1650	100	4000	6500	230.0	342.0	1.0	320	FNR-20K102
FNR-10K112	-40°C~+85°C	1100	680	895	1815	25	1250	2500	70.0	115.0	0.4	80	FNR-10K112
FNR-14K112	-40°C~+85°C	1100	680	895	1815	50	2500	4500	140.0	213.0	0.6	150	FNR-14K112
FNR-20K112	-40°C~+85°C	1100	680	895	1815	100	4000	6500	250.0	383.0	1.0	300	FNR-20K112
FNR-14K182	-40°C~+85°C	1800	1000	1465	2970	25	1250	2500	240.0	337.0	0.6	100	FNR-14K182
FNR-20K182	-40°C~+85°C	1800	1000	1465	2970	50	2500	4500	400.0	625.0	1.0	200	FNR-20K182
Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20µs)		Maximum Energy(J)		Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	8/20µs		2ms		(W)	(pF)	
FNR-25K470	-40°C~+85°C	47	30	38	89	40	1250		15		1.0	10000	FNR-25K470
FNR-32K470	-40°C~+85°C	47	30	38	89	40	2500		25		1.2	11000	FNR-32K470
FNR-40K470	-40°C~+85°C	47	30	38	89	40	5000		40		1.4	15000	FNR-40K470
FNR-25K560	-40°C~+85°C	56	35	45	106	40	1250		18		1.0	8000	FNR-25K560
FNR-32K560	-40°C~+85°C	56	35	45	106	40	2500		30		1.2	10000	FNR-32K560
FNR-40K560	-40°C~+85°C	56	35	45	106	40	5000		45		1.4	14000	FNR-40K560
FNR-25K680	-40°C~+85°C	68	40	56	129	40	1250		21		1.0	7000	FNR-25K680
FNR-32K680	-40°C~+85°C	68	40	56	129	40	2500		32		1.2	9000	FNR-32K680
FNR-40K680	-40°C~+85°C	68	40	56	129	40	5000		50		1.4	13000	FNR-40K680
FNR-25K820	-40°C~+85°C	82	50	65	156	200	5000		23		1.0	6000	FNR-25K820
FNR-32K820	-40°C~+85°C	82	50	65	156	200	10000		35		1.2	8000	FNR-32K820
FNR-40K820	-40°C~+85°C	82	50	65	156	200	20000		60		1.4	12000	FNR-40K820
FNR-25K101	-40°C~+85°C	100	60	85	190	200	5000		25		1.0	5000	FNR-25K101
FNR-32K101	-40°C~+85°C	100	60	85	190	200	10000		38		1.2	7000	FNR-32K101
FNR-40K101	-40°C~+85°C	100	60	85	190	200	20000		75		1.4	11500	FNR-40K101
FNR-25K121	-40°C~+85°C	120	75	100	216	200	5000		28		1.0	4000	FNR-25K121
FNR-32K121	-40°C~+85°C	120	75	100	216	200	10000		42		1.2	6000	FNR-32K121
FNR-40K121	-40°C~+85°C	120	75	100	216	200	20000		90		1.4	11000	FNR-40K121
FNR-25K151	-40°C~+85°C	150	95	125	270	200	5000		30		1.0	3000	FNR-25K151
FNR-32K151	-40°C~+85°C	150	95	125	270	200	10000		50		1.2	5000	FNR-32K151
FNR-40K151	-40°C~+85°C	150	95	125	270	200	20000		120		1.4	10500	FNR-40K151
FNR-25K201	-40°C~+85°C	200	130	170	360	200	5000		35		1.0	2400	FNR-25K201
FNR-32K201	-40°C~+85°C	200	130	170	360	200	10000		70		1.2	4700	FNR-32K201
FNR-40K201	-40°C~+85°C	200	130	170	360	200	20000		160		1.4	10000	FNR-40K201
FNR-25K221	-40°C~+85°C	220	140	180	385	200	5000		40		1.0	2200	FNR-25K221
FNR-32K221	-40°C~+85°C	220	140	180	385	200	10000		90		1.2	4300	FNR-32K221
FNR-40K221	-40°C~+85°C	220	140	180	385	200	20000		180		1.4	9500	FNR-40K221
FNR-25K241	-40°C~+85°C	240	150	200	420	200	5000		60		1.0	2000	FNR-25K241
FNR-32K241	-40°C~+85°C	240	150	200	420	200	10000		120		1.2	4000	FNR-32K241
FNR-40K241	-40°C~+85°C	240	150	200	420	200	20000		220		1.4	9000	FNR-40K241
FNR-25K271	-40°C~+85°C	270	175	225	473	200	5000		90		1.0	1700	FNR-25K271
FNR-32K271	-40°C~+85°C	270	175	225	473	200	10000		150		1.2	3500	FNR-32K271
FNR-40K271	-40°C~+85°C	270	175	225	473	200	20000		260		1.4	750	FNR-40K271

Part No.	Operating Temperature Range	Varistor Voltage	Maximum Operating Voltage		Maximum Clamping Voltage		Maximum Withstanding Surge Current(8x20μs)	Maximum Energy(J)	Maximum Rated Wattage	Capacitance (Reference) 1kHz	Warehouse Name*
		V(v)	AC (v)	DC(v)	VC(v)	IP(A)	8/20μs	2ms	(W)	(pF)	
FNR-25K361	-40°C~+85°C	360	230	300	612	200	5000	120	1.0	1400	FNR-25K361
FNR-32K361	-40°C~+85°C	360	230	300	612	200	10000	180	1.2	3000	FNR-32K361
FNR-40K361	-40°C~+85°C	360	230	300	612	200	20000	300	1.4	6000	FNR-40K361
FNR-25K391	-40°C~+85°C	390	250	320	663	200	5000	150	1.0	1200	FNR-25K391
FNR-32K391	-40°C~+85°C	390	250	320	663	200	10000	220	1.2	2500	FNR-32K391
FNR-40K391	-40°C~+85°C	390	250	320	663	200	20000	340	1.4	5000	FNR-40K391
FNR-25K431	-40°C~+85°C	430	275	350	731	200	5000	180	1.0	1100	FNR-25K431
FNR-32K431	-40°C~+85°C	430	275	350	731	200	10000	260	1.2	2250	FNR-32K431
FNR-40K431	-40°C~+85°C	430	275	350	731	200	20000	380	1.4	4500	FNR-40K431
FNR-25K471	-40°C~+85°C	470	300	380	799	200	5000	220	1.0	1000	FNR-25K471
FNR-32K471	-40°C~+85°C	470	300	380	799	200	10000	300	1.2	1900	FNR-32K471
FNR-40K471	-40°C~+85°C	470	300	380	799	200	20000	420	1.4	3600	FNR-40K471
FNR-25K621	-40°C~+85°C	620	385	505	1054	200	5000	260	1.0	1500	FNR-25K621
FNR-32K621	-40°C~+85°C	620	385	505	1054	200	10000	340	1.2	3200	FNR-32K621
FNR-40K621	-40°C~+85°C	620	385	505	1054	200	20000	450	1.4	3300	FNR-40K621
FNR-25K681	-40°C~+85°C	680	420	560	1160	200	5000	300	1.0	1200	FNR-25K681
FNR-32K681	-40°C~+85°C	680	420	560	1160	200	10000	380	1.2	3000	FNR-32K681
FNR-40K681	-40°C~+85°C	680	420	560	1160	200	20000	500	1.4	3000	FNR-40K681
FNR-25K751	-40°C~+85°C	750	460	615	1275	200	5000	350	1.0	1100	FNR-25K751
FNR-25K751	-40°C~+85°C	750	460	615	1275	200	10000	450	1.2	27000	FNR-25K751
FNR-25K751	-40°C~+85°C	750	460	615	1275	200	20000	550	1.4	2500	FNR-25K751
FNR-25K781	-40°C~+85°C	780	485	640	1326	200	5000	370	1.0	1050	FNR-25K781
FNR-32K781	-40°C~+85°C	780	485	640	1326	200	10000	480	1.2	2600	FNR-32K781
FNR-40K781	-40°C~+85°C	780	485	640	1326	200	20000	600	1.4	2450	FNR-40K781
FNR-25K821	-40°C~+85°C	820	510	670	1400	200	5000	400	1.0	1000	FNR-25K821
FNR-32K821	-40°C~+85°C	820	510	670	1400	200	10000	530	1.2	2400	FNR-32K821
FNR-40K821	-40°C~+85°C	820	510	670	1400	200	20000	640	1.4	2400	FNR-40K821
FNR-25K911	-40°C~+85°C	910	550	745	1550	200	5000	420	1.0	900	FNR-25K911
FNR-32K911	-40°C~+85°C	910	550	745	1550	200	10000	580	1.2	2200	FNR-32K911
FNR-40K911	-40°C~+85°C	910	550	745	1550	200	20000	700	1.4	2200	FNR-40K911
FNR-25K102	-40°C~+85°C	1000	625	825	1700	200	5000	450	1.0	800	FNR-25K102
FNR-32K102	-40°C~+85°C	1000	625	825	1700	200	10000	630	1.2	1900	FNR-32K102
FNR-40K102	-40°C~+85°C	1000	625	825	1700	200	20000	800	1.4	2000	FNR-40K102
FNR-25K112	-40°C~+85°C	1100	680	895	1870	200	5000	500	1.0	700	FNR-25K112
FNR-32K112	-40°C~+85°C	1100	680	895	1870	200	10000	700	1.2	1700	FNR-32K112
FNR-40K112	-40°C~+85°C	1100	680	895	1870	200	20000	850	1.4	1800	FNR-40K112
FNR-32K182	-40°C~+85°C	1800	1000	1465	3060	200	10000	750	1.2	1600	FNR-32K182
FNR-40K182	-40°C~+85°C	1800	1000	1465	3060	200	20000	1000	1.4	1600	FNR-40K182