

UT30C

Palm-Size Digital Multimeters



Registered Design No.: 9911180. 1M002

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/500V	±(0.8%+1)
AC Voltage	4V/40V/400V/500V	±(1.2%+3)
DC Current	400μA/4mA/40mA/400mA/10A	±(1%+2)
AC Current	400μA/4mA/40mA/400mA/10A	±(1.3%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Frequency	2kHz - 10MHz (Auto Ranging)	
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Data Hold	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	✓	
Auto Ranging	3999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	48 x 16mm
Product Colour	Body - Grey, Holster - Red
Product Net Weight	144g
Product Size	130 x 74 x 41mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Packing	Gift Box
Standard Quantity Per Carton	60 pcs
Standard Carton Measurement	500 x 300 x 290mm (0.0435 CBM per standard carton)
Standard Carton Gross Weight	Around 16.54kg

*Available at Extra Cost