


TOOLING NO. D-007 SR.TYPE A

REV.	DATE	DESCRIPTION	DESIGN	APPROVE
△	04/11/2000	CHANGE LENGTH		
△	10/06/2000	CHANGE LENGTH	陶彦军	
△	9/12/2003	ADD. WIRE COLOR	Patrick	



Pin Assignment

Conn.1	Conn.2	Color △
1	1	BLACK
2	6	BROWN
3	2	RED
4	8	ORANGE
5	9	YELLOW
6	7	GREEN
7	12	BLUE
8	11	PURPLE
9	13	WHITE
Shell	Shell	Drain Wire

Electronic Test :

1. Resistance : 2.0 Ω max
2. Resistance : 10M Ω Min
3. Hi-Pot : 300V DC/10ms

6	Outer Molded : 45P PVC , Color PMS 422U (Grey)	g
5	Inner Molded : PE.	g
4	Screw : #4-40	4
3	Connector : Hi-Density D-Sub 15P Male Solder Type,Blue.	1
2	Connector : D-Sub 9P Female Solder Type,Blue.	1
1	Cable : NON-UL 28AWG×9C Single Shield O.D=5.2MM,Jacket Color : PMS 422U (Grey)	1
NO	DESCRIPTION	QTY

ADACTUS		DESCRIPTION	DB9F/HD15M		
DRAW	Patrick	PART No.	ADA-2000-XX		
CHECK		DWG. No.	BA-30708	REV.	D
APP.		DATE	09/12/2003	SCALE	NONE
		SIZE	A4	UNIT	mm
				SHEET	1/1