



- **Wire** : PVC UL1803/18AWG
length : 1100±30mm
Out diameter : 3.50mm
Temperature tolerance range : -40°~105°
Braid copper wires : 170/0.08mm
- **Terminal** :
Right-angle 4mm brass (Nickel plated) banana plug with caged and insulated sheathing to avoid the brass oxidation.
- **Probe tip** :
4mm (gold plated) : AL-24A (AL-24 without alligator clip)
4mm (nickel plated) : AL-25A (AL-25 without alligator clip)
2mm (gold plated) : AL-26
- **Rating** :
IEC/EN 61010-031 : 2002
CAT III 1000V 10A / CAT IV 600V 10A



AL-24A

AL-25A

AL-26

AL-30, AL-30F



- The spring-shrouded 4mm brass caged banana probe tip.
- Double Insulated silicone wire 1m.
- Safety straight input plug.
- Rating : EN 61010-1 EN 61010-2-31 CAT III 1000V 10A.

AL-30R Red, AL-30B Black, AL-30G Green
<AL-30F> It is the fused version for AL-30.

- Fuse size : 6x32mm 6x46mm
- AL-30FR Red, AL-30FB Black**

AL-30A



- Wide grip alligator clips with integral finger guard, large 35mm high tension spring month.
- Double insulated silicone wire 1m.
- Safety straight input plug.
- Rating : EN 61010-1 EN 61010-2-31 CAT III 1000V 10A.

AL-30AR Red
AL-30AB Black
AL-30AG Green