


ARPV-24150 (24V, 6.25A, 150W)



Parameter standard:

Certificate		CE
Based on		IEC 61347
Input	Rated voltage:	AC170~250V
	Frequency:	50/60Hz
	Input power>Loading):	≤180W
Output	Output current (Loading):	DC 6.25A
	Output voltage (loading):	DC 24±0.5V
	Output voltage(no loading):	DC 24±0.5V
	Short-circuits protect:	Output shorted 3 seconds, and will work normally after separated.
	Over loading:	Protection
Voltage resistanse	Input-Output	AC 1.5kV/5mA 1min
	Input-Housing	AC 1.5kV/5mA 1min
Nonfunction	External appearance	1. The surface has no dirty vestige, rowing the wreath oxygen, transform 2. Power cable and the label paper to should 3. The date print clear
	Mark	The product label is right clear, neat, have no folding line
	Other	Whether manual and other related data are well-found or not
Ripple		≤600mVpp (120Hz)
To an electric voltage		≤10Vac
Protection grade		IP67
Working Temperature		-25°C~+40°C

Feature testing:

Testing Contents		Testing Qty				
Input voltage:		AC220V				
Testing Qty		1	2	3	4	5
Input power (Loading current 6.25A)		178W	177.4W			
Output voltage (Loading current 6.25A)		24.0V	23.9V			
Output voltage (Loading current 0A)		24.3V	24.3V			
High low pressure start		OK	OK			
Short-circuit:		OK	OK			
Bear the electric voltage	Input—Output:	OK	OK			
	Input—Housing:	OK	OK			
Over loading:		OK	OK			
Efficiency		81.6%	82.2%			
Verdict:		Pass				

- Housing Size (mm): L181×W29×H20
- Housing Material: AL
- Cable Model of input : VDE H03VV-F 3G0.75mm² black
- Cable Model of output: VDE H03VV-F 2*0.75mm² white
- Packing Size/Qty: 325×205×215mm / 50PCS