Crimping tools for other contacts

- Ratchet for precise crimping.
- Release option in the event of incorrect operation
- With stop for exact positioning of the contacts.

CTI 6 G

0,5...6 mm²



For PVC, PC, and polyamide insulated connectors 0.5...6 mm²

(~AWG 20 ... AWG 10)

• Parallel-crimp profile, for crimping contact and insulation in one step

CTI 6

0,5...6 mm²



For PVC, PC, and polyamide insulated connectors 0.5...6 mm²

(~AWG 20 ... AWG 10)

• Double-crimp profile, for crimping contact and insulation in one step





Technical data

Description of contact	
Type of contact	
Crimping range	mm ²
Crimping range 1 (with multiple crimping positions)	mm ²
Crimping range 2 (with multiple crimping positions)	mm ²
Crimping range 3 (with multiple crimping positions)	mm ²
Plug width	-
Tool data	
Length	mm
Weight	g
Note	

Ordering	data	

Orderii	ig uata		
Version			

Note			

CTI 6 G	
Insulated connector	
0.56	
0.51.5	
1.12.5	
2.66	
250	
747	

Туре	Qty	Order No.
CTI 6 G	1	9202850000

Additional accessories can be found in Chapter J.

CTI 6
Insulated connector
0.56
0.51.5
1.12.5
2.66
250
730

Туре	Qty	Order No.
CTI 6	1	9006120000

Additional accessories can be found in Chapter J.