

Cutting tools

- Easy handling because of automatic opening
- Safety lock reduces risk of injury
- Not suitable for steel wires, steel-armoured cables, aluminium alloys and hard-drawn copper conductors!



KT 14



-  max. 14 mm
-  max. 16 mm²
-  max. 35 mm²
-  max. 70 mm²

KT 20



-  max. 20 mm
-  max. 16 mm²
-  max. 35 mm²
-  max. 70 mm²

Technical data

Max. cutting performance, copper cable	
Solid (max. conductor cross-section)	mm ² /AWG
Stranded (max. conductor cross-section)	mm ² /AWG
Flexible (max. conductor cross-section)	mm ² /AWG
Flexible, stranded (max. conductor diameter)	mm
Max. cutting performance, aluminium cable	
Stranded (max. conductor cross-section)	mm ² /-
Stranded (max. conductor diameter)	mm
Solid	mm ²
Data / telephone / control cable	
Max. outer diameter	mm
Tool data	
Length / Width / Height	mm
Weight	g
Note	

Ordering data

Version
Note

KT14
16 / 6
35 / 2
70 / 2/0
14
70 / 2/0
14
35
14
215 / 66 / 28
320
Tool closed

Type	Qty	Order No.
KT 14	1	1157820000
Specifying	„solid-core aluminium cable“ corresponds to sector-shaped conductor with individual strands	

KT20
16 / 6
35 / 2
70 / 2/0
20
70 / 2/0
20
35
20
215 / 66 / 29
400
Tool closed

Type	Qty	Order No.
KT 20	1	9002300000
Specifying	„solid-core aluminium cable“ corresponds to sector-shaped conductor with individual strands	