



MY68

3 3/4 AUTORANGE DIGITAL MULTIMETER



FEATURES

- Conform to the IEC1010-1 standard CAT III 600V and CAT II 1000V
- SMT application
- Display: 3999 counts
- DC voltage: 400mV/4/40/400V \pm 0.7%, 1000V \pm 0.8%
- AC voltage: 400mV \pm 3.0%, 4/40/400V \pm 0.8%, 750V \pm 1.0%
- DC current: 400 μ /4000 μ /40m/400mA \pm 1.2%, 10A \pm 2.0%
- AC current: 400 μ /4000 μ /40m/400mA \pm 1.5%, 10A \pm 3.0%
- DC current (with clamp MS3302): 40A/400A(0.1A/1mV) \pm 0.8%
- AC current (with clamp MS3302): 40A/400A(0.1A/1mV) \pm 1.0%
- Resistance: 400/4k/40k/400k/4M Ω \pm 1.2%, 40M Ω \pm 2.0%
- Capacitance: 4nF \pm 5.0%, 40n/400n/4 μ /40 μ /200 μ F \pm 3.0%
- Frequency: 10/100/1000/10k/200kHz \pm 2.0%
- hFE: 1 ~ 1000
- Diode test
- Continuity test
- Auto power off
- Data hold
- Power: 6F22 (9V) x 1
- Size: 91mm x 189mm x 31.5mm
- Weight: Approx. 310g (including battery)