

MA SERIES P6BUI-XXXXXXZ 1KV ISOL. 1 W UNREG. DUAL SEPARATE OUTPUT DIP8

Available Inputs:

5, 12 and 24 VDC

Available Outputs:

(+/-) 3.3, 5, 7.2, 12, 15 and 18 VDC

Other specifications please enquire.

Electrical Specifications

(Typical at + 25° C, nominal input voltage, rated output current unless otherwise specified)

Input Specifications

Voltage range +/- 10 %
Filter Capacitors

Isolation Specifications

Rated voltage 1000 VDC
Leakage current 1 mA
Resistance 10⁹ Ohm
Capacitance 60 pF typ.

Output Specifications

Voltage accuracy +/- 5 %, max.
Ripple and noise (at 20 MHz BW) 100 mV p-p, max.
Short circuit protection Momentary
Line voltage regulation +/- 1,2 % / 1,0 % of Vin
Load voltage regulation +/- 8 %, load = 20 ~ 100 %
Temperature coefficient +/- 0,02 % / °C

General Specifications

Efficiency 75 % to 85 %
Switching frequency 80 KHz, typ.

Environmental Specifications

Operating temperature (ambient) - 40° C to + 85° C
Storage temperature - 55 °C to + 125 °C
Derating See graph
Humidity Up to 90 %, non condensing
Cooling Free air convection


Physical Characteristics

Dimensions DIP 12,7 X 10,16 x 6,85 mm
0,5 x 0,4 x 0,24 inches
Weight 1,8 g
Case material Non conductive black plastic


Examples of Partnumbers

PART NO.	INPUT VOLTAGE (VDC)	INPUT CURRENT NO LOAD	INPUT CURRENT FULL LOAD	OUTPUT VOLTAGE (VDC)	OUTPUT CURRENT (max. mA)	EFFICIENCY FULL LOAD (% TYP.)
P6BUI-050505Z	5	16	277	5/5	100/100	72
P6BUI-051515Z	5	20	262	15/15	35/35	80
P6BUI-120505Z	12	11	119	5/5	100/100	70
P6BUI-121212Z	12	10	125	12/12	50/50	80
P6BUI-121515Z	12	13	112	15/15	35/35	78
P6BUI-240505Z	24	6	54	5/5	100/100	76

Dimensions



Derating Graph and Pinning



Specification can be changed without notice.

Copyright PEAK electronics GmbH