

## HIGH ISOLATION VOLTAGE SINGLE TRANSISTOR TYPE MULTI OPTOCOUPLER SERIES

PS2561-1, -2, -4  
PS2561L-1, -2, -4

### FEATURES

- **HIGH ISOLATION VOLTAGE (BV)**  
5000 V<sub>r.m.s.</sub>: normal specification products
- **HIGH COLLECTOR TO EMITTER VOLTAGE**  
V<sub>CEO</sub> = 80 V MIN
- **HIGH CURRENT TRANSFER RATIO**  
CTR: 200% TYP
- **HIGH SPEED SWITCHING**  
t<sub>r</sub> = 3 μs, t<sub>f</sub> = 5 μs TYP
- **ISOLATED CHANNELS PER EACH PACKAGE**

### DESCRIPTION

PS2561-1, -2 and -4 and PS2561L-1, -2 and -4 are optically coupled isolators containing a GaAs light emitting diode and a NPN silicon phototransistor. PS2561-1, -2 and -4 are in a plastic DIP (Dual In-line Package) and PS2561L-1, -2 and -4 are in a lead bending type (Gull-wing) for surface mount.

### APPLICATIONS

Interface circuit for various instrumentations, and control equipment.




- AC LINE / DIGITAL LOGIC
- DIGITAL LOGIC / DIGITAL LOGIC
- TWISTED PAIR LINE RECEIVER
- TELEPHONE / TELEGRAPH LINE RECEIVER
- HIGH FREQUENCY POWER SUPPLY FEEDBACK CONTROL
- RELAY CONTACT MONITOR
- POWER SUPPLY MONITOR

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub> = 25°C)


		PART NUMBER			PS2561-1, -2, -4 PS2561L-1, -2, -4		
		SYMBOLS	PARAMETERS	UNITS	MIN	TYP	MAX
Diode	V <sub>F</sub>	Forward Voltage, I <sub>F</sub> = 10 mA		V		1.17	1.4
	I <sub>R</sub>	Reverse Current, V <sub>R</sub> = 5 V		μA			5
	C	Junction Capacitance, V = 0, f = 1.0 MHz		pF		50	
Transistor	I <sub>CEO</sub>	Collector to Emitter Dark Current, V <sub>CE</sub> = 40 V, I <sub>F</sub> = 0		nA			100
	BV <sub>CEO</sub>	Collector to Emitter Breakdown Voltage, I <sub>C</sub> = 1 mA, I <sub>B</sub> = 0		V	40	60	
	BV <sub>ECO</sub>	Emitter to Collector Breakdown Voltage, I <sub>E</sub> = 100 μA, I <sub>B</sub> = 0		V	7	9	
Coupled	CTR	Current Transfer Ratio <sup>1</sup> , I <sub>F</sub> = 5 mA, V <sub>CE</sub> = 5 V		%	80	200	400
	V <sub>CE(sat)</sub>	Collector Saturation Voltage, I <sub>F</sub> = 10 mA, I <sub>C</sub> = 2 mA		V			0.3
	R <sub>1-2</sub>	Isolation Resistance, V <sub>in-out</sub> = 1 k V		Ω	10 <sup>11</sup>		
	C <sub>1-2</sub>	Isolation Capacitance, V = 0, f = 1.0 MHz		pF		0.5	
	t <sub>r</sub>	Rise Time <sup>2</sup> , V <sub>CC</sub> = 10 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω		μs		3	
t <sub>f</sub>	Fall Time <sup>2</sup> , V <sub>CC</sub> = 10 V, I <sub>C</sub> = 2 mA, R <sub>L</sub> = 100 Ω		μs		5		

Note:

- CTR Rank (PS2561-1, PS2561L-1 Only)  
L: 200 to 400 %  
M: 80 to 240 %  
D: 100 to 300 %  
H: 80 to 160 %  
W: 130 to 260 %



- Test Circuit for Switching Time



**ABSOLUTE MAXIMUM RATINGS<sup>1</sup>** (T<sub>A</sub> = 25°C)


SYMBOLS	PARAMETERS	UNITS	RATINGS	
			PS2561 -1 PS2561L -1	PS2561 -2,-4 PS2561L -2,-4
Diode				
V <sub>R</sub>	Reverse Voltage	V	6	6
I <sub>F</sub>	Forward Current (DC)	mA	80	80
P <sub>D</sub>	Power Dissipation	mW/Ch	150	120
I <sub>F</sub> (PEAK)	Peak Forward Current (PW = 100 μs, Duty Cycle 1%)	A	1	1
Transistor				
V <sub>CEO</sub>	Collector to Emitter Voltage	V	80	80
V <sub>ECO</sub>	Emitter to Collector Voltage	V	7	7
I <sub>C</sub>	Collector Current	mA	50	50
P <sub>C</sub>	Power Dissipation	mW/Ch	150	120
Coupled				
BV	Isolation Voltage <sup>2</sup> normal spec	V <sub>r.m.s.</sub>	5000	5000
BV	Isolation Voltage <sup>2</sup> VDE0884 spec	V <sub>r.m.s.</sub>	3750	3750
P <sub>T</sub>	Total Power Dissipation	mW/Ch	250	200
T <sub>STG</sub>	Storage Temperature	°C	-55 to +150	-55 to +150
T <sub>OP</sub>	Operating Temperature	°C	-55 to +100	-55 to +100
T <sub>SOL</sub>	Lead Temperature (Soldering 10 s)	°C	260	260

Notes:


1. Operation in excess of any one of these parameters may result in permanent damage.
2. AC voltage for 1 minute at T<sub>A</sub> = 25 °C, RH = 60 % between input and output.

**TYPICAL PERFORMANCE CURVES** (T<sub>A</sub> = 25°)


**DIODE POWER DISSIPATION vs. AMBIENT TEMPERATURE**




**TRANSISTOR POWER DISSIPATION vs. AMBIENT TEMPERATURE**



**FORWARD CURRENT vs. FORWARD VOLTAGE**




**COLLECTOR CURRENT vs. COLLECTOR to EMITTER VOLTAGE**




**TYPICAL PERFORMANCE CURVES** ( $T_A = 25^\circ\text{C}$ )


**COLLECTOR TO EMITTER DARK CURRENT vs. AMBIENT TEMPERATURE**




**COLLECTOR CURRENT vs. COLLECTOR SATURATION VOLTAGE**




**NORMALIZED OUTPUT CURRENT vs. AMBIENT TEMPERATURE**




**CURRENT TRANSFER RATIO (CTR) vs. FORWARD CURRENT**



**SWITCHING TIME vs. LOAD RESISTANCE**





**SWITCHING TIME vs. LOAD RESISTANCE**




# PS2561-1, -2, -4 PS2561L-1, -2, -4

## TYPICAL PERFORMANCE CURVES (TA = 25°C)




## OUTLINE DIMENSIONS (Units in mm) DIP (Dual In-Line Package)


**PS2561-1**



**PS2561-2**




**PS2561-4**




**OUTLINE DIMENSIONS** (Units in mm) Lead Bending type (Gull-Wing)


**PS2561L-1**



**PS2561L-2**




**PS2561L-4**




**OUTLINE DIMENSIONS** (Units in mm) DIP (Lead-Bending Type)

**PS2561L1-1**



**PS2561L2-1**



EXCLUSIVE NORTH AMERICAN AGENT FOR **NEC** RF, MICROWAVE & OPTOELECTRONIC SEMICONDUCTORS

**CEL CALIFORNIA EASTERN LABORATORIES** • Headquarters • 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • Telex 34-6393 • FAX (408) 988-0279  
24-Hour Fax-On-Demand: 800-390-3232 (U.S. and Canada only) • Internet: <http://WWW.CEL.COM>

DATA SUBJECT TO CHANGE WITHOUT NOTICE

PRINTED IN USA ON RECYCLED PAPER -3/98