

## Series PVT412

Microelectronic Power IC

HEXFET® Power MOSFET Photovoltaic Relay  
Single Pole, Normally Open,  
0-400V, 140mA AC/DC

### General Description

The PVT412 Series Photovoltaic Relay is a single-pole, normally open solid-state relay that can replace electromechanical relays in many applications. It utilizes International Rectifier's proprietary HEXFET power MOSFET as the output switch, driven by an integrated circuit photovoltaic generator of novel construction. The output switch is controlled by radiation from a GaAlAs light emitting diode (LED) which is optically isolated from the photovoltaic generator.

These SSRs are specifically designed for worldwide telecom applications. PVT412L employs an active current-limiting circuitry enabling it to pass FCC Part 68 and other regulatory agency current surge requirements when overvoltage protection is provided. PVT412 does not employ the current-limiting circuitry and offers lower on-state resistance.


Series PVT412 Relays are packaged in a 6-lead molded DIP package with either through-hole or surface mount ('gull-wing') terminals. It is available in standard plastic shipping tubes or on tape-and-reel. Please refer to part identification information opposite.

### Applications

- On/Off Hook switch
- Dial-Out relay
- Ring relay
- General switching

### Features

- HEXFET Power MOSFET output
- Bounce-free operation
- 4,000 V<sub>RMS</sub> I/O isolation
- Load current limiting
- Linear AC/DC operation
- Solid-State Reliability
- UL recognized and BABT certified
- ESD Tolerance:
  - 4000V Human Body Model
  - 500V Machine Model



### Part Identification

PVT412L	current limit, through-hole
PVT412LS	current limit, surface-mount
PVT412LS-T	current limit, surface-mount, Tape and Reel
PVT412	no current limit, through-hole
PVT412S	no current limit, surface-mount
PVT412S-T	no current limit, surface-mount, Tape and Reel

## Series PVT412

International  
**IR** Rectifier




### Electrical Specifications (-40°C ≤ T<sub>A</sub> ≤ +85°C unless otherwise specified)

INPUT CHARACTERISTICS	Part Numbers		Units
	PVT412L	PVT412	
Minimum Control Current (see figures 1 and 2)	3.0		mA
Maximum Control Current for Off-State Resistance	0.4		mA
Control Current Range (Caution: current limit input LED, see figure 6)	3.0 to 25		mA
Maximum Reverse Voltage	7.0		V

OUTPUT CHARACTERISTICS	PVT412L		PVT412	Units
Operating Voltage Range	0 to ±400			V(DC or AC peak)
Maximum Load Current @ T <sub>A</sub> =+40°C 5mA Control (see figures 1 and 2)	A Connection	120	140	mA (AC or DC)
	B Connection	130	150	mA (DC)
	C Connection	200	210	mA (DC)
Maximum On-State Resistance @T <sub>A</sub> =+25°C For 50mA Pulsed Load, 5mA Control (see figure 4)	A Connection	35	27	Ω
	B Connection	18	14	Ω
	C Connection	9	7	Ω
Maximum Off-State Leakage @T <sub>A</sub> =+25°C, ±400V (see figure 5)	1.0			μA
Current Limit @T <sub>A</sub> =+25°C, For 5mA Control Current:	Connection:			
	Minimum		A	mA
	Maximum		C	mA
Complies with FCC Part 68 Surge Requirements*	yes		yes	
Maximum Turn-On Time @T <sub>A</sub> =+25°C (see figure 7) For 50mA, 100 V <sub>DC</sub> load, 5mA Control	2.0			ms
Maximum Turn-Off Time @T <sub>A</sub> =+25°C (see figure 7) For 50mA, 100 V <sub>DC</sub> load, 5mA Control	0.5			ms
Maximum Thermal Offset Voltage @ 5mA Control	0.5			μV
Maximum Output Capacitance @ 50V <sub>DC</sub>	12			pF

GENERAL CHARACTERISTICS	ALL MODELS		
Minimum Dielectric Strength, Input-Output	4000		V <sub>RMS</sub>
Minimum Insulation Resistance, Input-Output @T <sub>A</sub> =+25°C, 50%RH, 100V <sub>DC</sub>	10 <sup>12</sup>		Ω
Maximum Capacitance, Input-Output	1.0		pF
Maximum Pin Soldering Temperature (10 seconds maximum)	+260		°C
Ambient Temperature Range:	Operating	-40 to +85	
	Storage	-40 to +100	

## Connection Diagrams






Figure 1. Current Derating Curves\*




Figure 2. Current Derating Curves\*




Figure 3. Linearity Characteristics




Figure 4. Typical Normalized On-Resistance




Figure 5. Typical Normalized Off-State Leakage




Figure 6. Input Characteristics (Current Controlled)

\* Derating of 'B' and 'C' connection at +85°C will be 70% of that specified at +40°C and is linear from +40°C to +85°C.

# Series PVT412




Figure 7. Typical Delay Times




Figure 8. Delay Time Definitions





Figure 9. Typical Output Capacitance

## Case Outlines



01-2008 01

**Case Outlines**

