

# LED Power Supply

Automatic state identifying of  
Constant Current and Voltage



Model		SLP01SS	SLP03SS	SLP03SS1
Input		Input Voltage 100-240VAC 50Hz/60Hz		
Output	Constant Current	DC 350mA Voltage: 0.5V-4V	DC 350mA Voltage: 0.5V-4V	DC 700mA Voltage: 0.5V-4V
	Constant Voltage	DC 6V Current ≤ 300mA	DC 12V Current ≤ 300mA	DC 6V Current ≤ 650mA
Condition Temperature (Ta.)		Max. 50°C	Max. 50°C	Max. 50°C
The Highest Temperature of Surface (Tc.)		Max. 75°C	Max. 75°C	Max. 85°C
Insulation		IP65 cast resin on the case back	IP65 cast resin on the case back	IP65 cast resin on the case back
Dimension LxWxH (mm)		38x26.4x21	38x26.4x21	38x26.4x21
Thermal Protection		Yes	Yes	Yes
Short Circuit Protection		Yes	Yes	Yes
EMC Suppression		EN61347-2-13:2001 EN61347-1:2001		
LVD (safety) Conformity		EN55015 EN61547	EN61000-3-2 EN61000-3-3	

Sunrise Power Transformers GmbH  
Frankenstr. 35, D-20097, Hamburg

Tel. : +49-40-21983678  
Fax : +49-40-21983816

Email: info@sunrise-trafo.de  
Homepage: www.sunrise-trafo.de