



5.1V +8V REGULATOR WITH DISABLE AND RESET**ADVANCE DATA**

- OUTPUT CURRENTS UP TO 0.75A
- FIXED PRECISION OUTPUT 1 VOLTAGE $5.1V \pm 2\%$
- FIXED PRECISION OUTPUT 2 VOLTAGE $8V \pm 2\%$
- OUTPUT 1 WITH RESET FACILITY
- OUTPUT 2 WITH DISABLE BY TTL INPUT
- SHORT CIRCUIT PROTECTION AT BOTH OUTPUTS
- THERMAL PROTECTION
- LOW DROP OUTPUT VOLTAGE

**SIP9**
(Plastic Package)**ORDER CODE : TDA8133****DESCRIPTION**

The TDA8133 is a monolithic dual positive voltage regulator designed to provide fixed precision output voltages of 5.1V and 8V at currents up to 0.75A. An internal reset circuit generates a reset pulse when the output 1 decrease below the regulated voltage value. Output 2 can be disabled by TTL input. Short circuit and thermal protections are included in all the versions.


PIN CONNECTIONS

Tab. connected to Pin 5

8133-01.EPS

TDA8133

BLOCK DIAGRAM



8133-02 ERS

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{IN}	DC Input Voltage Pin 1	20	V
V_{DIS}	Disable Input Voltage	20	V
V_{RST}	Output Voltage at Pin 6	20	V
$I_{O1,2}$	Output Currents	Internally Limited	
P_t	Power Dissipation	Internally Limited	
T_{stg}	Storage Temperature	-65 to +150	°C
T_j	Junction Temperature	0 to +150	°C

8133-01 TBL

THERMAL DATA

Symbol	Parameter	Value	Unit
$R_{th(j-c)}$	Maximum Thermal Resistance Junction-case	8	°C/W
$R_{th(j-a)}$	Maximum Thermal Resistance Junction-ambient	60	°C/W
T_j	Maximum Recommended Junction Temperature	130	°C

8133-02 TBL

ELECTRICAL CHARACTERISTICS (V_{IN1} = 7V, V_{IN2} = 10V, T_j = 25°C, unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{O1}	Output Voltage	I _{O1} = 10mA	5	5.1	5.2	V
V _{O2}	Output Voltage	I _{O2} = 10mA	7.84	8	8.16	V
V _{O1}	Output Voltage	7V < V _{IN1} < 14V 10V < V _{IN2} < 14V	4.9		5.3	V
V _{O2}	Output Voltage	5mA < I _{O1,2} < 750mA	7.7		8.3	V
V _{IO1,2}	Dropout Voltage	I _{O1,2} = 750mA			1.4	V
V _{O1,2LI}	Line Regulation	7V < V _{IN1} < 14V 10V < V _{IN2} < 14V I _{O1,2} = 200mA			50 80	mV mV
V _{O1,2LO}	Load Regulation	5mA < I _{O1} < 0.6A 5mA < I _{O2} < 0.6A			100 160	mV mV
I _Q	Quiescent Current	I _{O1} = 10mA Output 2 Disabled			2	mA
V _{O1RST}	Reset Threshold Voltage	K = V _{O1}	K - 0.4	K - 0.25	K - 0.1	V
V _{RTH}	Reset Threshold Hysteresis	See circuit description	20	50	75	mV
t _{RD}	Reset Pulse Delay	C _e = 100nF See circuit description		25		ms
V _{RL}	Saturation Voltage in Reset Condition	I _S = 5mA			0.4	V
I _{RH}	Leakage Current in Normal Condition at Pin 6	V _S = 10V			10	µA
K _{O1,2}	Output Voltage Thermal Drift	T _j = 0 to 125°C $K_O = \frac{\Delta V_O \cdot 10^6}{\Delta T \cdot V_O}$		100		ppm/°C
I _{O1,2SC}	Short Circuit Output Current	V _{IN1} = 7V, V _{IN2} = 10V V _{IN1,2} = 16V (see Note)			1.6 1	A A
V _{DISH}	Disable Voltage High (out 2 active)		2			V
V _{DISL}	Disable Voltage Low (out 2 disabled)				0.8	V
I _{DIS}	Disable Bias Current	0V < V _{DIS} < 7V	-100		2	µA
T _{jsd}	Junction Temperature for Thermal Shut Down			145		°C

8133-03.TBL

Note : Safe permanent short-circuit is only guaranteed for input voltages up to 16V.

CIRCUIT DESCRIPTION

The TDA8133 is a dual voltage regulator with Reset and Disable.

The two regulation parts are supplied from one voltage reference circuit trimmed by zener zap during EWS test.

Since the supply voltage of this last is connected at Pin 1 (V_{IN1}), the regulator 2 will not work if Pin 1 is not supplied.

The outputs stage have been realized in darlington configuration with a drop typical 1.2V.

The disable circuit, switch-off the output 2 if a voltage lower than 0.8V is applied at Pin 4.

The Reset circuit checks the voltage at the output 1. If this one goes below V_{OUT} - 0.25V (4.85V typ.), the comparator "a" (see Figure 1) discharges rapidly the capacitor C_e and the reset output goes at once Low. When the voltage at the out1 rises above V_{OUT} - 0.2V (4.9V typ.), the voltage V_{Ce} increases linearly to 2.5V corresponding to a delay

$$t_d \text{ following the law : } t_d = \frac{C_e \cdot 2.5V}{10\mu A} \text{ (see Figure 2),}$$

then the reset output goes high again. To avoid gliches in the reset output, the second comparator "b" has a large hysteresis (1.9V).

TDA8133

Figure 1







Figure 2



TYPICAL APPLICATION



PACKAGE MECHANICAL DATA
9 PINS - PLASTIC SIP


Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			7.1			0.280
a1	2.7		3	0.106		0.118
B			24.8			0.976
b1		0.5			0.020	
b3	0.85		1.6	0.033		0.063
C		3.3			0.130	
c1		0.43			0.017	
c2		1.32			0.052	
D			21.2			0.835
d1		14.5			0.571	
e		2.54			0.100	
e3		20.32			0.800	
L	3.1			0.122		
L1		3			0.118	
L2		17.6			0.693	
L3			0.25			0.010
M		3.2			0.126	
N		1			0.039	

PM-SIP9-EPS

SIP9-TBL

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No licence is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

Purchase of I²C Components of SGS-THOMSON Microelectronics, conveys a license under the Philips I²C Patent. Rights to use these components in an I²C system, is granted provided that the system conforms to the I²C Standard Specifications as defined by Philips.

SGS-THOMSON Microelectronics GROUP OF COMPANIES
 Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco
 The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.